

MID-RISE SCISSORS SMART LIFT

The MRL09 showcase an innovative two-stage runway design, creating a discreet low-profile entrance for a wide range of vehicles to enter from either side, accommodating low clearance cars. Ease to use, barely maintenance required, it's the ideal mid-rise quick service lift.



MRL09

Main Features


- ✓ 9,000lbs lifting capacity.
- ✓ Mid rise scissors lift, 24V safety voltage control.
- ✓ Dual hydraulic synchronization & hydraulic locking system;
- ✓ The lifting scissors are made of thickened steel which is more strong;
- ✓ Adjustable lift platform length, applicable to vehicles with different wheelbases;
- ✓ Two-stage drive-in ramps, suitable for lifting ultra-low chassis vehicles;
- ✓ Flexible structure design, users can choose either flush mount or surface mount installation;
- ✓ Standard ETL certificated power unit;
- ✓ AMGO global 5-3-2 warranty policy:
5 year Warranty on Steel Components,
3 year Warranty on Hydraulic Parts,
2 years Warranty on Electrical Components.



Dual hydraulic synchronization & hydraulic locking system;




Adjustable lift platform length, applicable to vehicles with different wheelbases.



Both 1 1/2" and 3" height rubber pads included as standard supply.



SPECIFICATIONS



Model	MRL09
Lifting Capacity	9,000lbs
Lifting Time	30S
Max. Lifting Height	A 47 1/4"
Minimum Height	B 5 1/2"
First Stage Ramp Height	C 2 3/4"
Overall Length(Inc. ramps)	D 157 1/16"
Overall Width	E 76 3/4"
Width Between Runways	F 29 1/2"
Runway Length	G 61 3/8"-77 1/8"
Gross Weight	1,788 lbs
Motor	2.0HP,220V/60Hz,single phase

AMGO HYDRAULIC CORPORATION

SC Division: 1931 Joe Rogers Jr Blvd, Manning, SC 29102, USA
Tel:(803)505-6410

TX Division: 4310 Adler, Suite 200, Dallas, TX 75211,USA
Tel:(214)377-7742