

TWO-POST SUPER ASYMMETRIC LIFT

This versatile design optimizes space utilization in your shop or garage. It features standard two height settings to fit different ceiling heights and incorporates Super Asymmetric technology for convenient symmetric or asymmetric loading. At a 9000lbs capacity, its sturdy structure also supports extra width and height extension, catering versatile needs to enthusiasts.



6-HO

Main Features

- ✓ Lifting capacity: 9,000 lbs;
- ✓ Dual hydraulic direct-driven cylinders made on high standard;
- ✓ The **SuperAsymmetric** can load the vehicle in either a symmetrical or an asymmetrical way, ensuring adequate door clearance ;
- ✓ Single-point manual safety lock release, simultaneously unlock both columns from one side;
- ✓ Clear-floor design, provide unobstructed floor use;
- ✓ Overhead safety shut-off device prevents vehicle damage;
- ✓ Standard two height settings accommodate varying ceiling heights;
- ✓ Self-lubricating UHMW polyethylene sliders• Automatic arms restraint;
- ✓ Aero sync cables come as standard;
- ✓ Comes with detachable toe guard and tool tray;
- ✓ Standard double-screw rubber pad (pin dia 1/2") with 3" extension adapters.



The optional saddle adapter.
Kits No.:1102185008C



Standard double-screw rubber pad (pin dia 1/2") with 3" extension adapters.



Automatic arm restraints



SuperAsymmetric arms allow to load different vehicles in an asymmetric or symmetric configuration.




Single point safety release makes it easier for operators to unlock both columns from one column.



Hydraulic Direct-driven Cylinders.

SPECIFICATIONS



Model	OH-9
Lifting Capacity	9,000 lbs
Lifting Time	57s
Max. Lifting height: (w/o extension adapter)	71 5/8"~73 9/16"
Max. Lifting height: (w/ extension adapter)	74 5/8"~76 9/16"
Max. lock height: (w/o extension adapter)	69 13/16"~71 11/16"
Max. lock height: (w/ extension adapter)	72 13/16"~74 11/16"
Overall Height:(low setting)	142 1/2"
Overall Height:(high setting)	150 1/2"
Overall Width	C 135"
Drive-Thru Clearance	D 99 1/2"
Width Between Columns	E 112 3/16"
Minimum Pad Height	F 3 3/4"
Gross Weight	1,369 lbs
Motor	2.0HP, 220V 60Hz, single phase

AMGO HYDRAULIC CORPORATION

SC Division: 1931 Joe Rogers Jr Blvd, Manning, SC 29102, USA
Tel:(803)505-6410

TX Division: 4310 Adler, Suite 200, Dallas, TX 75211,USA
Tel:(214)377-7742