



TWO-POST HEAVY-DUTY LIFTS

AMGO's latest OH-18 boasts heavy-duty construction, offering immense lifting capacity up to 18000lbs. It features long, sturdy carriages for enhanced stability and is equipped with two types of rubber pads to suit various vehicles. Moreover, it incorporates AMGO's 3in1 technology for effortless height setting.



OH-18

TWO POST LIFT

Main Features

- ✓ Lifting capacity: 18,000 lbs;
- ✓ Dual hydraulic direct-driven cylinders made on high standard;
- ✓ 4 two-stage sturdy arms ensure the heavy load stability;
- ✓ Single-point manual safety lock release, simultaneously unlock both columns from one side;
- ✓ Clear-floor design, provide unobstructed floor use;
- ✓ Overhead safety shut-off device prevents vehicle damage;
- ✓ Exclusive: adjustable three height setting accommodates varying service ceiling heights;
- ✓ Extremely long carriages are equipped to enhance the stability and durability;
- ✓ Self-lubricating UHMW polyethylene sliders
- ✓ Automatic arms restraint;
- ✓ Areo sync cables come as standard;
- ✓ Comes with detachable toe guard and tool tray;
- ✓ Both heavy-duty single-screw rubber pad and saddle adapter come as standard;
- ✓ Both 3" and 6" extension adapters come as standard.



Single point safety release makes it easier for operators to unlock both columns from one column.



Hydraulic Direct-driven Cylinders.



Both heavy duty single-screw rubber pads and saddle adapters come as standard.



Both 3" and 6" extension adapters come as standard.




Automatic arm restraints



Equipped with extremely long carriages to enhance the stability.

SPECIFICATIONS



Model	OH-18
Lifting Capacity	18,000 lbs
Lifting Time	84s
Max. Lifting height: (w/o extension adapter)	74 7/8"~76 1/4"
Max. Lifting height: (w/ extension adapter)	83 7/8"~85 1/4"
Max. lock height: (w/o extension adapter)	72 15/16"~74 1/4"
Max. lock height: (w/ extension adapter)	81 15/16"~83 1/4"
Overall Height:(low setting)	174"
Overall Height:(Medium setting)	186"
Overall Height:(High setting)	198"
Overall Width	C 150 3/4"
Drive-Thru Clearance	D 110 7/16"
Width Between Columns	E 123 1/2"
Minimum Pad Height	F 6 7/8"
Gross	2,787 lbs
Motor	2.0HP, 220V 60Hz, single phase

AMGO HYDRAULIC CORPORATION

SC Division: 1931 Joe Rogers Jr Blvd, Manning, SC 29102, USA
Tel: (803)505-6410

TX Division: 4310 Adler, Suite 200, Dallas, TX 75211, USA
Tel: (214)377-7742

